

MILLAT MF 455 Specifications

PERFORMANCE

Max Hp (kW) power	C ISO hp (kW)	100 (74)
Max Torque	@ 1400 rpm	415
Rated engine speed		2200

ENGINE

Type		1104.4C
No. of Cylinders		4
Capacity	cc	4400
Aspiration		Turbo

TRANSMISSION

12 x 4 Side Shift		●
-------------------	--	---

POWER TAKE OFF

Live Single Speed		●
-540 rpm		
IPTO Single Speed	Cab/Platform	●/○
-540 rpm		
IPTO Single Speed		○
-540/1000 rpm		

HYDRAULICS

3-Point Linkage Control		Mechanical
Lift Capacity	max kgf	2500
Oil Flow	litres/min	17
System Pressure	bar	210
Auxiliary Hydraulics		
Oil Flow	litres/min	42
System Pressure	bar	170

STEERING

Hydrostatic		●
-------------	--	---

SPOOL VALVES

Capacity	Cab/Platform	● 2 Valves ● 1 Valve
----------	--------------	-------------------------

BRAKES

Type		Oil immersed
------	--	--------------

STANDARD WHEELS AND TYRES

Front 2wd/4wd		9.00-16/14.9-24
Rear		18.4-34

WEIGHT AND DIMENSIONS

Without Ballast Cab/Platform	kg	4,460/4,070
Length	mm	4,270
Height Over Exhaust	mm	2,640
Wheel Base	mm	2,370

CAPACITIES

Fuel Tank	Litres	100.0
Engine oil	Litres	8.0
Transmission oil	Litres	46.0

For even greater productivity a range of optional equipments is available including front weights, rear-wheel weights, two - post folding ROPS frame. For full details please consult your Massey Ferguson dealer.

- = Standard
- = Optional
- = Not applicable/available
- C = ISO TR14396



Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies errors or omissions may occur and details of the specification may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer of Distributor prior to any purchase.